Configuracion nginx

#user nginx; worker_processes 2;

#error_log /var/log/nginx/error.log; #error_log /var/log/nginx/error.log notice; #error_log /var/log/nginx/error.log info;

#pid /var/run/nginx.pid;

include /etc/nginx/modules.conf.d/*.conf;

events {

```
  worker_connections  2048;
```

}

http {

```
  include       mime.types;
  default_type  application/octet-stream;
```

```
  #log_format  main  '$remote_addr - $remote_user [$time_local] "$request" '
  #                  '$status $body_bytes_sent "$http_referer" '
  #                  '"$http_user_agent" "$http_x_forwarded_for"';
```

```
  #access_log  /var/log/nginx/access.log  main;
```

```
  sendfile        on;
  #tcp_nopush     on;
```

```
  #keepalive_timeout  0;
  keepalive_timeout  65;
  #tcp_nodelay        on;
  proxy_buffering on;
  proxy_buffer_size 128k;
  proxy_buffers 4 256k;
  proxy_busy_buffers_size 256k;**

  #gzip  on;
  #gzip_disable "MSIE [1-6]\.(?!.*SV1)";
```

```
  server_tokens off;
```

```
  include /etc/nginx/conf.d/*.conf;
```

}

override global parameters e.g. worker_rlimit_nofile include /etc/nginx/*global_params;

From:
https://wiki.merkatu.info/ - **Wiki de merkatu**

Permanent link:
https://wiki.merkatu.info/configuracion_nginx?rev=1499344144

Last update: **2017/07/06 14:29**