Configuracion nginx

#user nginx; worker_processes 2;

#error_log /var/log/nginx/error.log; #error_log /var/log/nginx/error.log notice; #error_log /var/log/nginx/error.log info;

#pid /var/run/nginx.pid;

include /etc/nginx/modules.conf.d/*.conf;

events {

```
    worker_connections  2048;
```

}

http {

```
    include       mime.types;
    default_type  application/octet-stream;
```

```
    #log_format  main  '$remote_addr - $remote_user [$time_local] "$request" '
    #                  '$status $body_bytes_sent "$http_referer" '
    #                  '"$http_user_agent" "$http_x_forwarded_for"';
```

```
    #access_log  /var/log/nginx/access.log  main;
```

```
    sendfile        on;
    #tcp_nopush     on;
```

```
    #keepalive_timeout  0;
    keepalive_timeout  65;
    #tcp_nodelay        on;
```

proxy_buffering on; proxy_buffer_size 128k; proxy_buffers 4 256k; proxy_busy_buffers_size 256k;

```
    #gzip  on;
    #gzip_disable "MSIE [1-6]\.(?!.*SV1)";
```

```
    server_tokens off;
```

```
    include /etc/nginx/conf.d/*.conf;
```

}

override global parameters e.g. worker_rlimit_nofile include /etc/nginx/*global_params;

From:

https://wiki.merkatu.info/ - **Wiki de merkatu**

Permanent link:

https://wiki.merkatu.info/configuracion_nginx?rev=1499344638

Last update: **2017/07/06 14:37**